Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-557-9302

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.344 inches

Flat Height:

0.219 inches

Body Diameter:

3.469 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.250 inches

Body Length:

4.500 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Screw Thread Diameter:

Between 0.190 inches and 0.375 inches

Screw Thread Series Designator:

Unef and unf

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

4

Mounting Method:

Locking bushing and unthreaded hole

Electrical Resistance Per Section:

75.000 ohms 2nd section

Power Dissipation Rating Per Section In Watts:

100.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Standard Taper Curve Per Section:

A single section

Special Features:

Mtg holes on 0.688 in. By 3.625 in. Mtg centers



Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0