

View Online at <https://aerobasegroup.com/nsn/5905-00-560-8186>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.312 inches

**First Flat Length:**

0.375 inches

**Flat Height:**

0.216 inches

**Body Diameter:**

1.125 inches

**Shaft Diameter:**

Between 0.249 inches and 0.251 inches

**Shaft Length:**

Between 0.781 inches and 0.844 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.500 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.516 inches and 0.547 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

250.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Fixed Tap Quantity Per Section:**

1 single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Tap Location From Ccw Terminal Per Section In Ohms:**

125000.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0