Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-561-1300

Section 0	Quantity:
1	
Body Sty	le:
Cylindrica	1
Reliabilit	y Indicator:
Not estab	lished
Overall L	ength:
0.519 incl	nes
Body Dia	meter:
0.718 incl	nes
Mounting	Stud Length:
Between	0.025 inches and 0.250 inches
Body Ler	ngth:
0.255 incl	nes
Overall D	iameter:
0.718 incl	nes
Actuator	Туре:
Integral k	hob
Effective	Electrical Rotation In Deg Angular Rotation:
260.0	
Screw Th	read Diameter:
0.073 incl	nes
Screw Th	read Series Designator:
Unf	
Screw Th	ready Qty Per Inch (tpi):
72.0	
Mounting	Facility Quantity:
2	
Terminal	Location:
Rear end	
Mounting	Method:
Threaded	stud
Electrica	Resistance Per Section:
500.0 ohr	ns single section
Rotary A	ctuator Travel In Angular Deg:
260.0	
Ambient	Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
85.0 singl	e section
Power Di	ssipation Rating Per Section In Watts:
0.10 free	air single section
Resistan	ce Tolerance Per Section In Percent:

-20.0 to 20.0 single section

NSN 5905-00-561-1300

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0