

View Online at <https://aerobasegroup.com/nsn/5905-00-562-3510>

**Section Quantity:**

1

**Body Style:**

Cylindrical tab/flange mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 0.820 inches and 0.840 inches

**Body Diameter:**

Between 0.365 inches and 0.375 inches

**Mounting Hole Diameter:**

0.075 inches

**Body Length:**

Between 0.616 inches and 0.626 inches

**Overall Diameter:**

Between 0.365 inches and 0.375 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

330.0

**Lateral Distance Between Mounting Hole Centers:**

0.640 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

4.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

100.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0 to 30.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Includes 1/2 in. Snap-in shaft

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0