NSN 5905-00-564-3023

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-564-3023 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Body Length:** 0.375 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 8.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity: 3 tab, solder lug

NSN 5905-00-564-3023

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarization:

No

Fiig:

A002a0