Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-564-6081

| Section | Quantity: |
|---------|-----------|

1

- Body Style: Rectangular w/mounting holes
- **Reliability Indicator:**
- Not established
- Terminal Length:
- 0.160 inches
- Mounting Hole Diameter:
- 0.072 inches
- Shaft Diameter:
- 0.093 inches
- Shaft Length:
- 0.375 inches
- Body Length:
- 0.375 inches
- **Body Width:**
- 0.182 inches
- Body Height:
- 0.375 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 5400.0
- **Center To Center Distance Between Terminals:**
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.419 inches
- Mounting Facility Quantity:
- 2
- Terminal Location:
- Lower adjacent side two rows
- Mounting Method:
- Unthreaded hole
- Center To Center Distance Between Terminal Rows:
- 0.100 inches
- **Electrical Resistance Per Section:**
- 20.000 kilohms single section
- **Rotary Actuator Travel In Angular Deg:**

5400.0



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0