NSN 5905-00-564-7313

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-564-7313

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
0.259 inches
Body Width:
0.594 inches
Body Height:
0.813 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Terminal Location:
Front end
Mounting Method:
Tab
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a

N/a

NSN 5905-00-564-7313

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0