

View Online at https://aerobasegroup.com/nsn/5905-00-568-2204

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-30.0/+30.0

#### **Electrical Resistance:**

1.740 kilohms

#### **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

#### **Inclosure Method:**

Encased

## **Terminal Type:**

\_ . . . .

# Tab, solder lug

**Reliability Indicator:** 

#### Established

**Reliability Failure Rate Level In Percent:** 

0.010

## **Terminal Length:**

0.438 inches

## **Body Length:**

1.062 inches

#### **Body Width:**

0.531 inches

#### **Body Height:**

0.562 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.719 inches

## **Power Dissipation Rating In Watts:**

8.000 free air

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.781 inches

#### **Terminal Width:**

0.140 inches

## Mounting Hole Size:

0.125 inches

#### Style Designator:

Axial terminal (s)

#### **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



**Specification Data:** 

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0