

View Online at <https://aerobasegroup.com/nsn/5905-00-569-5562>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.9630 inches and 0.9680 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

Between 0.963 inches and 0.973 inches

Undercut Width:

Between 0.0005 inches and 0.0006 inches

Body Diameter:

1.062 inches

Mounting Hole Diameter:

0.125 inches

Angle Of Mounting Hole In Deg:

120.0

Angle Between Centerlines Of Mounting Holes In Deg:

60.0

Shaft Diameter:

0.125 inches

Shaft Length:

0.688 inches

Body Length:

0.625 inches

Mounting Lip Diameter:

Between 1.0570 inches and 1.0670 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0620 inches

Mounting Hole/stud Circle Diameter:

1.000 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

100.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

6.250 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

1.5 free air all sections

Fixed Tap Quantity Per Section:

1 all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

25.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0