

View Online at <https://aerobasegroup.com/nsn/5905-00-569-5827>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.719 inches

Body Diameter:

Between 1.995 inches and 2.005 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.657 inches and 0.719 inches

Mounting Bushing Length:

0.312 inches

Body Length:

1.031 inches

Overall Diameter:

2.375 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

28.000 kilohms single section

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-0.25/+0.25 ohms single section

Resistance Tolerance Per Section In Percent:

-25.0/+25.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

14000.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

80.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0