

View Online at <https://aerobasegroup.com/nsn/5905-00-569-5827>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.719 inches

**Body Diameter:**

Between 1.995 inches and 2.005 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

Between 0.657 inches and 0.719 inches

**Mounting Bushing Length:**

0.312 inches

**Body Length:**

1.031 inches

**Overall Diameter:**

2.375 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

Between 0.526 inches and 0.536 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

28.000 kilohms single section

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-0.25/+0.25 ohms single section

**Resistance Tolerance Per Section In Percent:**

-25.0/+25.0 single section

**Tap Location From Ccw Terminal Per Section In Ohms:**

14000.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

80.0 single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0