

View Online at https://aerobasegroup.com/nsn/5905-00-572-3463

## Section Quantity:

2

**Body Style:** 

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

2.189 inches

## First Flat Length:

0.438 inches

## Flat Height:

0.105 inches

## Body Diameter:

0.125 inches

## Shaft Diameter:

0.250 inches

## Shaft Length:

0.969 inches

# Mounting Bushing Length:

0.375 inches

# Body Length:

1.220 inches

## **Overall Diameter:**

1.460 inches

## Shaft Style:

Round, flatted

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Maximum Starting Torque:

0.20 inch-ounces

## Maximum Running Torque:

0.20 inch-ounces

## **Nonturn Device Location:**

At 2'30 oclock

# Nonturn Device Radius:

0.312 inches

## Shaft End Play:

0.00300 inches

# Shaft Runout:

0.001 inches



# **Shaft Radial Play:** 0.003 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0