## NSN 5905-00-572-4274

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-572-4274 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.656 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.906 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.000 inches **Body Length:** 1.625 inches **Overall Diameter:** 1.109 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.70 inch-ounces

Maximum Running Torque:
0.60 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces

## NSN 5905-00-572-4274

3 turret

**Specification Data:** 

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
1.5
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

## NSN 5905-00-572-4274

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Li	fe:
----------	-----

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0