

View Online at <https://aerobasegroup.com/nsn/5905-00-573-1854>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

Between 0.1000 inches and 0.1100 inches

Undercut Diameter:

2.960 inches

Undercut Width:

0.0800 inches

Body Diameter:

3.000 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

Between 0.2495 inches and 0.2497 inches

Shaft Length:

1.000 inches

Body Length:

2.438 inches

Mounting Lip Diameter:

2.9370 inches

Mounting Lip Depth:

0.0750 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Shaft End Play:

0.00200 inches

Shaft Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

25.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

6.0 free air all sections

Function Conformity Per Section:

All sections absolute conformity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections 360 degrees sine-cosine

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0