

View Online at <https://aerobasegroup.com/nsn/5905-00-573-1855>

**Section Quantity:**

4

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

Between 0.1000 inches and 0.1100 inches

**Undercut Diameter:**

2.960 inches

**Undercut Width:**

0.0800 inches

**Body Diameter:**

3.000 inches

**Angle Of Mounting Hole In Deg:**

90.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

Between 0.249 inches and 0.2497 inches

**Shaft Length:**

1.000 inches

**Body Length:**

2.438 inches

**Mounting Lip Diameter:**

2.9370 inches

**Mounting Lip Depth:**

0.0750 inches

**Mounting Hole/stud Circle Diameter:**

Any acceptable

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Shaft End Play:**

0.00200 inches

**Shaft Runout:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

25.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.00 to 1.00 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

6.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections 360 degrees sine-cosine

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Terminal Type And Quantity:**

24 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0