## NSN 5905-00-574-2137

**Section Quantity:** 

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-574-2137

| Rectangular w/mounting holes                    |
|---|
| Reliability Indicator:                          |
| Not established                                 |
| Overall Length:                                 |
| 0.757 inches                                    |
| Terminal Length:                                |
| 0.172 inches                                    |
| Overall Height:                                 |
| Between 0.490 inches and 0.510 inches           |
| Overall Width:                                  |
| Between 0.180 inches and 0.230 inches           |
| Shaft Diameter:                                 |
| Between 0.058 inches and 0.098 inches           |
| Shaft Length:                                   |
| 0.045 inches                                    |
| Body Length:                                    |
| 0.540 inches                                    |
| Body Width:                                     |
| Between 0.180 inches and 0.230 inches           |
| Body Height:                                    |
| Between 0.490 inches and 0.510 inches           |
| Shaft Style:                                    |
| Round, slotted                                  |
| Actuator Type:                                  |
| Single shaft                                    |
| Maximum Running Torque:                         |
| 5.00 inch-ounces                                |
| Center To Center Distance Between Terminals:    |
| Between 0.090 inches and 0.110 inches           |
| Lateral Distance Between Mounting Hole Centers: |
| 0.520 inches                                    |
| Terminal Location:                              |
| Lower adjacent side single row                  |
| Mounting Method:                                |
| Terminal  |
| Electrical Resistance Per Section:              |
| 200.000 ohms single section                     |
| Rotary Actuator Travel In Angular Deg:          |
| Between 7200.0 and 16200.0                      |
|   |

## NSN 5905-00-574-2137

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Center | To Center | Distance | Retween | Center | Terminal        | And (  | Jutside ' | Terminal:      |
|--------|-----------|----------|---------|--------|-----------------|--------|-----------|----------------|
| Center | 10 Center | Distance | Detween | Center | i ei iiiiiiai . | Allu ( | Juisiue   | i ei iiiiiiai. |

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## **Test Data Document:**

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-27208/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0