## NSN 5905-00-574-2140

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-574-2140

View Online at https://aerobasegroup.com/nsn/5905-00-574-2140		
Section Quantity:		
1		
Body Style:		
Rectangular w/mounting holes		
Overall Length:		
0.712 inches		
Terminal Length:		
0.172 inches		
Overall Height:		
Between 0.490 inches and 0.510 inches		
Overall Width:		
Between 0.180 inches and 0.230 inches		
Shaft Diameter:		
Between 0.058 inches and 0.098 inches		
Shaft Length:		
0.045 inches		
Body Length:		
0.540 inches		
Body Width:		
Between 0.180 inches and 0.230 inches		
Body Height:		
Between 0.490 inches and 0.510 inches		
Shaft Style:		
Round, slotted		
Actuator Type:		
Single shaft		
Maximum Running Torque:		
5.00 inch-ounces		
Center To Center Distance Between Terminals:		
Between 0.090 inches and 0.110 inches		
Lateral Distance Between Mounting Hole Centers:		
0.520 inches		
Terminal Location:		
Lower adjacent side single row		
Mounting Method:		
Terminal		
Electrical Resistance Per Section:		
500.000 ohms single section		
Rotary Actuator Travel In Angular Deg:		
Between 7200.0 and 16200.0		
Center To Center Distance Between Center Terminal And Outside Terminal:		
Between 0.090 inches and 0.110 inches		

Between 0.090 inches and 0.110 inches

## NSN 5905-00-574-2140

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Sec	tion At Zero Percent Rated Power:
150.0 single section	

**Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** 

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Test Data Document:** 

81349-mil-r-27208-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0