

View Online at <https://aerobasegroup.com/nsn/5905-00-574-2353>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.940 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.590 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0