NSN 5905-00-575-0345

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-575-0345 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 2.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.645 inches **Undercut Diameter:** 2.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 1.020 inches **Overall Diameter:** 3.406 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 357.0 **Maximum Starting Torque:**

1.30 inch-ounces

Maximum Running Torque:

0.70 inch-ounces

NSN 5905-00-575-0345

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.010 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.175/+0.175 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
6.9 7th secondary quality
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock 6th primary
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
+0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Precious Material And Location:
Terminals gold
Precious Material:
riecious material.
Gold Gold
Gold
Gold Terminal Type And Quantity:

NSN 5905-00-575-0345

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0