NSN 5905-00-575-8857

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-575-8857 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 2.125 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Fixed Tap Quantity Per Section:** 1 single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Tap Location From Ccw Terminal Per Section In Ohms:** 2500.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-575-8857

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0