NSN 5905-00-575-9050

Non-wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-575-9050

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Overall Length:
1.370 inches
Body Diameter:
1.156 inches
Shaft Diameter:
Between 0.248 inches and 0.252 inches
Shaft Length:
Between 0.705 inches and 0.745 inches
Mounting Bushing Length:
Between 0.480 inches and 0.520 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section

70.0 single section

NSN 5905-00-575-9050

Non-wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
C single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0