## NSN 5905-00-577-0767

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-0767 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.625 inches Flat Height: 0.216 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.625 inches **Body Length:** 1.500 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

**Electrical Resistance Per Section:** 2.500 kilohms single section **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section

## NSN 5905-00-577-0767

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Q	esistance	Tolerance	Per Section	In P	ercent.
7	esisiance	i olei alice	rei Section	шг	ercent.

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0