Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-0877

### Section Quantity:

1

Body Style: Cylindrical bushing mounted

Reliability Indicator:

Not established

**Body Diameter:** 

0.875 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

# 0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.281 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Rear end

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

5.000 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0