Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-1692

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.690 inches

Body Diameter:

1.590 inches

Shaft Diameter:

0.250 inches

Shaft Length:

2.500 inches

Mounting Bushing Length:

Between 0.360 inches and 0.390 inches

Body Length:

0.940 inches

Overall Diameter:

2.135 inches

Shaft Style:

Round, slotted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

117.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 230.0 and 275.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 20.000 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 280.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Switch Current Type And Rating In Amps: 3.000 ac **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 eyelet **Specification Data:** 81349-mil-r-19/3 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: