NSN 5905-00-577-2000

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-2000

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.750 inches
Body Diameter:
0.750 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.375 inches
Overall Diameter:
0.906 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.375 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section

NSN 5905-00-577-2000

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating	Per	Section	In	watts:
0 E fron air aingle co	ction				

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

F single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0