Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-2190

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.703 inches

### **Body Diameter:**

0.906 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

1.250 inches

### Mounting Bushing Length:

# 0.500 inches

**Body Length:** 

0.453 inches

### Shaft Style:

Round, slotted

### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

Between 251.0 and 318.0

#### Maximum Starting Torque:

6.00 inch-ounces

### Maximum Running Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

128.00 inch-ounces

#### **Nonturn Device Location:**

At 9 oclock

#### Nonturn Device Radius:

0.438 inches

### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0



#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Locking bushing

## Features Provided:

Shaft locking device

### **Electrical Resistance Per Section:**

2.5 megohms single section

#### **Rotary Actuator Travel In Angular Deg:**

Between 251.0 and 318.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

#### Power Dissipation Rating Per Section In Watts:

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/4 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

```
Demilitarization:
```

No

Fiig:

A002a0