## NSN 5905-00-577-2796

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-2796 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.484 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.234 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference 200.000 ohms single section

**Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 

**Rotary Actuator Travel In Angular Deg:** 

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## NSN 5905-00-577-2796

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No