Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-2830

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.062 inches and 1.312 inches **Body Diameter:** Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches **Body Length:** Between 0.468 inches and 0.656 inches **Overall Diameter:** 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.515 inches and 0.547 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing

NSN 5905-00-577-2830

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:

1.5 megohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0