## NSN 5905-00-577-2950

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-2950 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.938 inches **Body Length:** 0.391 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5905-00-577-2950

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0