NSN 5905-00-577-3611



| View Online | at https://aerobasegroup.com/nsn/5905-00-577-3611 |
|----------------|---|
| Section Qua | ntitv: |
| 1 | |
| Body Style: | |
| Cylindrical bu | ushing mounted |
| Reliability In | dicator: |
| Not establish | ed |
| Overall Leng | gth: |
| Between 2.93 | 37 inches and 3.187 inches |
| Body Diame | ter: |
| Between 1.03 | 32 inches and 1.156 inches |
| Shaft Diame | ter: |
| Between 0.2 | 48 inches and 0.251 inches |
| Shaft Lengtl | 1: |
| Between 2.4 | 69 inches and 2.531 inches |
| Mounting B | ushing Length: |
| Between 0.34 | 44 inches and 0.390 inches |
| Body Lengtl | n: |
| Between 0.4 | 68 inches and 0.656 inches |
| Overall Dian | neter: |
| 1.515 inches | |
| Shaft Style: | |
| Round, slotte | ed |
| Actuator Ty | pe: |
| Single shaft | |
| Maximum St | earting Torque: |
| 6.00 inch-our | nces |
| Maximum S | top Torque: |
| 128.00 inch- | punces |
| Nonturn Day | vice Location: |

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-577-3611

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 35.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 309.0 and 320.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Specification Data: |
| 81349-mil-r-94/5 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |