NSN 5905-00-577-3975



| ection Quantity: ody Style: ylindrical bushing mounted eliability Indicator: ot established verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches founting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted ctuator Type: | |
|--|--|
| ylindrical bushing mounted eliability Indicator: ot established verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| ylindrical bushing mounted eliability Indicator: ot established verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| eliability Indicator: ot established verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| ot established verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches ounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| verall Length: etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches ounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 1.312 inches and 1.562 inches ody Diameter: etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches ounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 1.032 inches and 1.156 inches haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| haft Diameter: etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.486 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Length: etween 0.485 inches and 0.656 inches lounting Bushing Lengt | |
| etween 0.248 inches and 0.251 inches haft Length: etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| haft Length: etween 0.844 inches and 0.906 inches founting Bushing Length: etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 0.844 inches and 0.906 inches lounting Bushing Length: etween 0.485 inches and 0.515 inches lounting Bushing Length: etween 0.486 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| counting Bushing Length: etween 0.485 inches and 0.515 inches cody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 0.485 inches and 0.515 inches ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| ody Length: etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| etween 0.468 inches and 0.656 inches verall Diameter: 515 inches haft Style: ound, slotted | |
| verall Diameter: 515 inches haft Style: ound, slotted | |
| 515 inches haft Style: ound, slotted | |
| haft Style: ound, slotted | |
| ound, slotted | |
| | |
| ctuator Type: | |
| | |
| ingle shaft | |
| aximum Starting Torque: | |
| 00 inch-ounces | |

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-577-3975

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 309.0 and 320.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| 10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Specification Data: |
| 31349-mil-r-94/5 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| |