Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-7130

# Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.281 inches and 1.375 inches Body Diameter: Between 0.890 inches and 0.922 inches Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.844 inches and 0.906 inches

Mounting Bushing Length:

0.375 inches

**Body Length:** 

Between 0.437 inches and 0.469 inches

**Overall Diameter:** 

1.274 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.422 inches and 0.454 inches

Screw Thread Diameter:

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

# NSN 5905-00-577-7130

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



#### **Electrical Resistance Per Section:**

500.0 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

Between 251.0 and 318.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

#### **Actuator Travel Control Feature:**

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-94/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0