NSN 5905-00-577-7508

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-7508 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.290 inches First Flat Length: 0.620 inches Flat Height: 0.216 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.880 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.410 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:**

Standard bushing

NSN 5905-00-577-7508

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 1.000 ohms single section Power Dissipation Rating Per Section In Watts: 25.0 free air single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A002a0