## NSN 5905-00-577-7544



Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-577-7544 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.566 inches

**Shaft Style:** 

Round, slotted

**Actuator Type:** 

Single shaft

**Nonturn Device Location:** 

At 12 oclock

**Nonturn Device Radius:** 

0.157 inches

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

10.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## NSN 5905-00-577-7544

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 binding post
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No