Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-7697

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.495 inches

#### Body Diameter:

1.590 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.620 inches

#### **Overall Diameter:**

2.060 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

Between 280.0 and 305.0

#### Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

128.00 inch-ounces

#### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Lower adjacent side single row



# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

150.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 305.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-19/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0