Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-7709

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.093 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

3.000 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

## 0.562 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

# Nonturn Device Radius:

0.281 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

2.000 kilohms single section

## Power Dissipation Rating Per Section In Watts:

5.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0