Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-577-9612

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

### Mounting Hole Diameter:

0.090 inches

Shaft Diameter:

0.098 inches

Shaft Length:

0.062 inches

Body Length:

1.266 inches

Body Width:

# 0.220 inches

**Body Height:** 

0.312 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

### **Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:** 

2

Terminal Location:

Rear end

### **Mounting Method:**

Unthreaded hole

### **Electrical Resistance Per Section:**

10.000 kilohms single section

## Rotary Actuator Travel In Angular Deg:

360.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0 to 25.0 single section

## Power Dissipation Rating Per Section In Watts:

0.8 free air single section



**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## Actuator Travel Control Feature:

Continuous motion

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0