NSN 5905-00-577-9827

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-577-9827

Electrical Resistance: 300.000 ohms Resistance Tolerance In Percent: 5.000/#5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/#35.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Retiability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 1.470 inches and 0.230 inches Rody Longth: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: Selest Percentage of Terminal Council of Terminal Counci	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 300,000 ohms Resistance Tolerance In Percent: 5,000/45,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40,00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40,00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40,00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40,00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55,0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wive lead Reliability Indicator: Not established Terminal Length: Between 1,370 inches and 1,620 inches Body Diameter: Between 0,170 inches and 0,230 inches Body Length: Between 0,470 inches and 0,250 inches Power Dissipation Rating In Watts: 3,000 free air Style Designator: Avial terminal each end Test Data Document: 104813-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Via Unit of Measure:	
Resistance Tolerance in Percent: 5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 4.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 4.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 4.0.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0.4-350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.470 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating in Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: Style Designator: Avial terminal each end Test Data Document: Shelf Life: Via Unit Of Measure: — Demilitarization: No	
Ambient Tempurature in Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 40.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.170 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Langth: Between 0.470 inches and 0.560 inches Power Dissipation Rating in Watts: 3.000 free air Style Designator: Akail terminal each end Test Data Document: 96481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: — Demilitarization: No	600.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Realiability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Between 1.370 inches and 0.230 inches Between 0.170 inches and 0.230 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Via Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Realiability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Between 1.370 inches and 0.230 inches Between 0.170 inches and 0.230 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Via Unit Of Measure:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Bedy Length: Between 0.170 inches and 0.230 inches Bedy Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 106481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	40.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.470 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: Decklar-122465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; accludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No	340.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Bedween 1.370 inches and 1.620 inches Beddy Diameter: Between 0.470 inches and 0.230 inches Boddy Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avaid terminal each end Fest Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Unit Of Measure: — Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3,000 free air Style Designator: Axial terminal each end Test Data Document: 106481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-55.0/+350.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 106481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Encapsulated
Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No	Terminal Type:
Note stablished Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No	Wire lead
Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: D6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 0.6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Not established
Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Length:
Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 1.370 inches and 1.620 inches
Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Diameter:
Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.170 inches and 0.230 inches
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:
3.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.470 inches and 0.560 inches
Axial terminal each end Test Data Document: D6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: D6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	3.000 free air
Test Data Document: 06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
D6481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No	06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A001a0	A001a0