NSN 5905-00-577-9988

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-577-9988

Electrical Resistance: 1.210 megohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Iterminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 4.000/41,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.188 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.000 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/6 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0