Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-578-3536

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.250 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

# 0.250 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

# Nonturn Device Location:

At 12 oclock

### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

#### **Screw Thread Series Designator:**

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

60.0 ohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

25.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

### Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

### Fiig:

A002a0