## NSN 5905-00-578-4393

Precision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-578-4393



**Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.087 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.688 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 5400.0 **Maximum Starting Torque:** 2.75 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Un Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 5400.0

## NSN 5905-00-578-4393

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Power Dissipation Rating Per Section In Watts:
13.8 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: