NSN 5905-00-578-9051



Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque:	View Online at htt	ps://aerobasegroup.com/nsn/5905-00-578-9051
Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Section Quantity	:
Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	1	
Reliability Indicator: Not established Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.486 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Body Style:	
Not established Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Cylindrical bushin	g mounted
Overall Length: Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Reliability Indica	tor:
Between 1.062 inches and 1.312 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Not established	
Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Overall Length:	
Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 1.062 in	ches and 1.312 inches
Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Body Diameter:	
Between 0.248 inches and 0.251 inches Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 1.032 in	ches and 1.156 inches
Shaft Length: Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Shaft Diameter:	
Between 0.594 inches and 0.656 inches Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 0.248 in	ches and 0.251 inches
Mounting Bushing Length: Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Shaft Length:	
Between 0.485 inches and 0.515 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 0.594 in	ches and 0.656 inches
Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Mounting Bushii	ng Length:
Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 0.485 in	ches and 0.515 inches
Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Body Length:	
1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Between 0.468 in	ches and 0.656 inches
Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Overall Diameter	:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	1.515 inches	
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Shaft Style:	
Single shaft Maximum Starting Torque: 6.00 inch-ounces	Round, slotted	
Maximum Starting Torque: 6.00 inch-ounces	Actuator Type:	
6.00 inch-ounces	Single shaft	
	Maximum Startir	g Torque:
Maximum Stop Torque:	6.00 inch-ounces	
	Maximum Stop T	orque:

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-578-9051

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
C single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.

Fiig:

A002a0