Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-578-9191

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.625 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

0.562 inches

## Shaft Style:

Round, slotted, knurled

### Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Lower adjacent side single row

# Mounting Method:

Standard bushing

# Electrical Resistance Per Section:

50.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

## Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0