## NSN 5905-00-581-0102

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-581-0102

Electrical Resistance:  11.300 kilohms  Resistance Tolerance In Percent:  1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+15.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:  2.000 free air  Style Designator:
Resistance Tolerance In Percent:  1.1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:
Resistance Tolerance In Percent:  1.1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:  10.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0  Inclosure Method:  Incapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:
Informer Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0  Inclosure Method:  Encapsulated  Incriminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  10.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:  2.000 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:  2.000 free air
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air
Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length: 2.188 inches  Power Dissipation Rating In Watts:
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 2.188 inches Power Dissipation Rating In Watts:
Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 2.188 inches  Power Dissipation Rating In Watts:
Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 2.188 inches  Power Dissipation Rating In Watts: 2.000 free air
Not established  Body Diameter:  0.375 inches  Body Length:  2.188 inches  Power Dissipation Rating In Watts:  2.000 free air
Body Diameter:  0.375 inches  Body Length: 2.188 inches  Power Dissipation Rating In Watts:  2.000 free air
0.375 inches  Body Length: 2.188 inches  Power Dissipation Rating In Watts: 2.000 free air
Body Length: 2.188 inches Power Dissipation Rating In Watts: 2.000 free air
2.188 inches  Power Dissipation Rating In Watts: 2.000 free air
Power Dissipation Rating In Watts: 2.000 free air
2.000 free air
Style Designator:
orgin designator.
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/6 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0