## NSN 5905-00-581-0511

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-581-0511

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0620 inches
Overall Length:
1.531 inches
Undercut Diameter:
1.063 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Body Length:
0.781 inches
Overall Diameter:
1.625 inches
Mounting Lip Diameter:
1.2340 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
196.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:

1.00 inch-ounces

## NSN 5905-00-581-0511

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.0045 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
100.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
69.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

## NSN 5905-00-581-0511

Precision Wire Wound Variable Resistor - Page 3 of 3



Ambient	Tempurature	In Deg Celsi	us Per Sect	ion At Full	Rated Power:

40.0 single section

**Terminal Type And Quantity:** 

4 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0