NSN 5905-00-581-0700

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-0700 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.297 inches **Body Diameter:** 1.150 inches **Shaft Diameter:** 0.250 inches Shaft Length: 0.625 inches **Mounting Bushing Length:** 0.438 inches **Body Length:** 0.672 inches **Overall Diameter:** 1.527 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:**

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

NSN 5905-00-581-0700

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissi	pation Ra	tina Per	Section I	n Watts:
I OWO DIGGI	pation ita		0000011	watto.

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0