NSN 5905-00-581-1214

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-581-1214

Electrical Resistance: 11.000 kilohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Not established Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Body Diameter: 0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
0.469 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Body Length: 0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
0.560 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end
14.000 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
81349-milr26-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0