## NSN 5905-00-581-2845

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-2845

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Body Diameter:  |
| 0.280 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 1.625 inches  |
| Mounting Bushing Length:                                  |
| 0.375 inches  |
| Body Length:  |
| 0.620 inches  |
| Shaft Style:  |
| Round   |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:                                  |
| At 9 oclock   |
| Nonturn Device Radius:                                    |
| 0.531 inches  |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:                        |
| 500.0 ohms single section                                 |
| Power Dissipation Rating Per Section In Watts:            |
| 2.0 free air single section                               |
| Resistance Tolerance Per Section In Percent:              |
| -5.0 to 5.0 single section                                |

A single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-581-2845

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Termi  | nal T | Гуре   | And | Quant | ity: |
|--------|-------|--------|-----|-------|------|
| 3 tab, | solo  | ler lu | q   |       |      |

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0