NSN 5905-00-581-3279

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-3279 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.255 inches **Body Length:** 2.156 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.530 inches **Screw Thread Diameter:** 0.500 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 55.0 ohms 2nd section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air 2nd section

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 all sections

NSN 5905-00-581-3279

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No