NSN 5905-00-581-3634

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-581-3634 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 3.3110 inches and 3.1200 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 3.312 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 3.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 4.188 inches **Mounting Lip Diameter:** 3.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:**

3.50 inch-ounces **Maximum Running Torque:** 2.50 inch-ounces **Shaft End Play:** 0.003 inches **Shaft Runout:** 0.002 inches

NSN 5905-00-581-3634

Lateral Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.003 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1350.0 single section and 4500.0 single section and 7650.0 single section
Rotary Actuator Travel In Angular Deg:
9000.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
11.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
3 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-581-3634

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0